

VISQUEEN CROPTIGHT

Geresnis augalų onservavimas

„Visqueen Croptight“ yra polietileno plėvelė, pakeičianti ritinių vyniojimo tinklą. Ji ne tik efektyviai suformuoja ritinius, bet taip pat spartina žolės silosavimo procesą, nes sudaro geresnį deguonies barjerą, kadangi naudojami papildomi plėvelės sluoksniai.

„Visqueen Croptight“ galima naudoti norint užkonservuoti keliais rūšis, įskaitant žolę, kukurūzus ir cukrinių runkelių išspaudas. Naudojant „Visqueen Croptight“ pagaminami geresnės kokybės pašarai, kuriuos yra lengviau sušerti ir tvarkyti. Kadangi ji taip pat pagaminta iš polietileno, plėvelę „Visqueen Croptight“ galima perdirbtį kartu su siloso vyniojimo plėvele.

- Geresnis deguonies barjeras,
- Spatesnis fermentavimo procesas,
- Kompaktiškesni ir stabilesni ryšuliai,
- Lengva tvarkyti ir sandėliuoti,
- Mažesni pašarų nuostoliai,
- Galima automatiškai tiekti pašarų ryšlius,
- Lengva perdirbti.



www.croptight.com



Geresnis augalų onservavimas

VISQUEEN
CROPTIGHT

Designed for next generation combi-wrappers

The advanced manufacturing methods used in the production of Visqueen Croptight 5 layer pre-orientated net replacement film ensure the production of a high performance film designed for use on next generation combi-wrappers with Film&Film wrapping capability.

Enhanced oxygen barrier

The additional layers of Visqueen Croptight around the circumference of the bale provide an increased oxygen barrier to enhance crop conservation, improve silage quality and reduce moulds.

Excellent puncture resistance

Visqueen Croptight is manufactured using 5 layer blown film extruders and pre-orientated technology to give it excellent puncture resistance - especially beneficial when baling stalky crops.

Improved bale edge protection

Designed to cover the full width of the bale, Visqueen Croptight offers additional protection around the edges of the bale, which is essential when baling heavy or dry crops.

Better shaped bales

As a film rather than a net product, Visqueen Croptight also helps bales retain their shape more effectively thanks to greater surface area coverage.

Automated bale feeding

Bales wrapped using Visqueen Croptight can be opened easily and mechanically with modern bale shears which allow the bales to be opened and fed directly into the mix wagon in one process.

Smooth film surface

The smooth surface of Visqueen Croptight reduces wastage of useable silage, as, unlike netwrap, no baled fodder can become enmeshed in it. This feature is especially useful on frosty, winter morning when the film just peels away smoothly from the ensiled fodder.

Recycling made easier

Visqueen Croptight's production from the same material as balewrap means that it doesn't have to be separated from balewrap after use. Both Visqueen Croptight and the accompanying bale wrap can be recycled together saving valuable time and labour.

Polythene sleeve packaging

Visqueen Croptight is supplied in a fully recyclable polythene sleeve that provides protection to the reel during transit and loading whilst detailing product information and usage instructions.



Specification

Panaudojimas	Plotis (mm)	Storis (μm)	Ilgis (m)	Ričių skaičius paletėje (#)	Paletės matmenys (cm)	Paletės Aukštis (m)
Ne UV Stabilizuotas						
Cukriniai runkeliai / Kukurūzai/TMR	950	13	2400	20	112 x 130	± 1.10
Cukriniai runkeliai / Kukurūzai/TMR	1280	13	2400	20	112 x 130	± 1.10
Žolės	1280	16	2000	20	112 x 130	± 1.10
Žolės	1380	16	2000	20	112 x 147	± 1.10
Haylage	1380	20	1650	20	114 x 147	± 1.10
UV Stabilizuotas						
Haylage	1280	20	1650	20	112 x 130	± 1.10

Visqueen Croptight is manufactured in an ISO 9001 and ISO 14001 accredited facility.

Visqueen Croptight 13μm and 16μm should not be used on hay or straw and should only be used in conjunction with a balewrap such as Visqueen Polycrop or Visqueen PolycropPro. It has not been designed to be used alone due to limited UV stability.



@polycrop

E: info@polycrop.com

www.croptight.com